

## Stainless Steel Tracer Wire



### **DESCRIPTION & FEATURES :**

**Specification:** Non-UL listed tracer wire specifically developed for Horizontal Directional Drilling application.

**Service:** Natural gas PE pipe tracer wire; direct buried installation for horizontal-directional drill (HDD) use.

**Wire Material:** 304 Stainless Steel Alloy, 49 strands, annealed.

**Rating:** 30 Volts maximum. 1700 lb. yield.

**Length:** 500 and 1,000 feet spools. Random or special reel lengths available on request

### **Insulating Jacket**

**Material:** High Molecular Weight, High Density Polyethylene (HMW-HDPE).

**Thickness:** 0.045 inch minimum (45 mil.)

**Rating:** 30 Volts maximum.

**Color:** Available in multiple colors to suit your needs

**Markings:** Physical, permanent markings: surface legend print on insulating jacket to repeat at minimum interval of every two linear feet.

1. Company identification.
2. Gas pipe line warning indication
3. Wire type.
4. Insulating jacket material identification "
5. HDD DIRECT BURIAL USE ONLY" label

"GAS PIPE TRACER WIRE,  
STRANDED SS /45 MIL HMW-HDPE,  
30 VOLT, HDD DIRECT BURIAL USE ONLY"

**Packaging:** Wire wound on a compact metal or wooden spool.  
500', 1,000', 2,500' REELS STANDARD, AVAILABLE IN LENGTHS UP TO 10,000'

## Stainless Steel Tracer Wire



Size	Strands	Breaking Strength Stainless Steel (lbs.)	HMW- HDPE (in)	Weight/1000'
3/32"	7x7 (49)	920	.045	16
1/8"	7x7 (49)	1700	.045	28
5/32"	7x7 (49)	2400	.045	43
3/16"	7x7 (49)	3700	.045	62
1/4"	7x19 (133)	6100	.045	110